



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

K2K-20

Assembly and contact grease VP 924

ELKALUB VP 924 is a universal assembly grease based on mineral oil. The grease facilitates various assembly processes and is suitable for the lubrication of sliding movements (e.g. guides, spindles, insertion ends of SDS tools). Due to its water-repellent properties and its strong adhesion, ELKALUB VP 924 protects against corrosion. In another application, ELKALUB VP 924 can be used to protect battery poles, pole terminals and electric plug connections. The grease shows good compatibility with the vast majority of plastics and sealing materials (except EPDM). ELKALUB VP 924 is available in a user-friendly brush can, which allows an economical, precise and clean application.

BASE OIL mineral oil

THICKENER Inorganic

VISCOSITY 460 mm²/s

OPERATING TEMPERATURE -20 °C bis 120 °C

NLGI CLASS 2

FIELD OF USE

- fittings

BUSINESS

- Automotive
- miscellaneous

FUNCTIONALITY

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- assembly grease
- Contact lubricant

PACKING

- 50 g tube
 - 200 ml brush box
 - 5 kg bucket
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com