



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KP2K-10

Grease for the food industry GLS 364 H1 Halal



ELKALUB GLS 364 is a high-performance lubricating grease for application in the food industry. The product is mainly used for the lubrication of antifriction bearings under low load and high speed indexes (ndm > 600.000). ELKALUB GLS 364 is very resistant to water and steam as well as to acid solutions (e.g. fruit acids), alkaline media (e.g. cleansing agents) and salt water. ELKALUB GLS 364 protects efficiently against corrosion. The product is well conveyable in central lubricating systems and miscible with conventional soap greases.

BASE OIL White oil

THICKENER polyurea

VISCOSITY 72 mm²/s

OPERATING TEMPERATURE -10 °C bis 120 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings
- Guides & Curves

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

BUSINESS

- Food
- beverages
- Pharma & Medicine
- bearing manufacturer

FUNCTIONALITY

- Food grease

PACKING

- 250 g tube
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com