



KPIK-10

## Grease for the food industry GLS 367/N1

ELKALUB GLS 367/N1 is a partly synthetic lubricating grease for application in the food industry. The product is extremely adhesive and is suitable for slow-turning antifriction bearings, for slip motions and for the lubrication of chains, valves, spindles, sterilizers etc. ELKALUB GLS 367/N1 is resistant to water (up to +100 °C) as well as to acids and alkalis. ELKALUB GLS 367/N1 is suitable for temperatures from -10 °C up to +130 °C (short-time up to 180 °C). A H1-registration for this penetration class would be possible.

**BASE OIL** White oil Other**THICKENER** Inorganic**VISCOSITY** 165 mm<sup>2</sup>/s**OPERATING TEMPERATURE** -10 °C bis 130 °C**NLGI CLASS** 1**FIELD OF USE**

- roller bearing
- bearings
- racks
- Linear guides & ball screws
- valves
- fittings

**BUSINESS**

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Food
- beverages
- Pharma & Medicine
- Wood
- bearing manufacturer

---

#### FUNCTIONALITY

- assembly grease
- Food grease

---

#### PACKING

- 250 g tube
  - 400 g cartridge
  - 5 kg bucket
  - 18 kg hobbock
  - 50 kg hobbock
  - 150 kg barrel
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)