



KP1K-10

Grease for the food industry GLS 367/N1

ELKALUB GLS 367/N1 is a partly synthetic lubricating grease for application in the food industry. The product is extremely adhesive and is suitable for slow-turning antifriction bearings, for slip motions and for the lubrication of chains, valves, spindles, sterilizers etc. ELKALUB GLS 367/N1 is resistant to water (up to +100 °C) as well as to acids and alkalis. ELKALUB GLS 367/N1 is suitable for temperatures from -10 °C up to +130 °C (short-time up to 180 °C). A H1-registration for this penetration class would be possible.

BASE OIL White oil Other

THICKENER Inorganic

viscosity 165 mm²/s

OPERATING TEMPERATURE -10 °C bis 130 °C

NLGI CLASS 1

FIELD OF USE

- roller bearing
- bearings
- racks
- Linear guides & ball screws
- valves
- fittings

BUSINESS

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



- Food
- beverages
- Pharma & Medicine
- Wood
- bearing manufacturer

FUNCTIONALITY

- assembly grease
- Food grease

PACKING

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr