



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KP2K-10

Grease for the food industry GLS 367/N2 H1 Halal



ELKALUB GLS 367/N2 is a partly synthetic lubricating grease for application in the food industry. The product is extremely adhesive and is suitable for slow-turning antifriction bearings, for slip motions and for the lubrication of chains, valves, spindles, sterilizers etc. ELKALUB GLS 367/N2 is resistant to water (up to +100 °C) as well as to acids and alkalis. ELKALUB GLS 367/N2 is suitable for temperatures from -10 °C up to +130 °C (short-time up to 180 °C).

BASE OIL White oil Other

THICKENER Inorganic

VISCOSITY 155 mm²/s

OPERATING TEMPERATURE -10 °C bis 130 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings
- racks
- Linear guides & ball screws

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- valves
- fittings

BUSINESS

- Food
- beverages
- Pharma & Medicine
- Power Tools
- bearing manufacturer

FUNCTIONALITY

- assembly grease
- Food grease

PACKING

- 250 g tube
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com