



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KP1K-20

Grease for the food industry GLS 380/N1

ELKALUB GLS 380/N1 is a partly synthetic special grease for plain and antifriction bearings (mainly plain bearings with pairings of nonferrous metals and steel) as well as for chains in the temperature range from -10 °C up to +120 °C. ELKALUB GLS 380/N1 is extremely resistant to water (also sea water) and one of the remarkable features of this grease is its excellent adhesive strength. ELKALUB GLS 380/N1 is also applicable in the presence of alcohol*. ELKALUB GLS 380/N1 possesses the USDA H1 approval and is suitable for lubricating areas, where incidental food contact is possible. Note that the dynamic stability (ndm-factor) drops off considerably under the influence of water and at the same time higher temperatures. ELKALUB GLS 380/N1 is not resistant to acids and alkalis and should not be mixed with other greases.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL White oil Poly-alpha-olefin

THICKENER Aluminum complex solid lubricants

VISCOSITY 72 mm²/s

OPERATING TEMPERATURE -25 °C bis 120 °C

NLGI CLASS 1

FIELD OF USE

- roller bearing
- bearings

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Guides & Curves

BUSINESS

- bearing manufacturer
- plant construction

FUNCTIONALITY

- Low-temperature grease

PACKING

- 250 g tube
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com