

**KFHC0M-30**

Grease for plastic-steel pairings VP 905

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL ester Poly-alpha-olefin

THICKENER lithium solid lubricants

VISCOSITY 360 mm²/s

OPERATING TEMPERATURE -30 °C bis 120 °C

NLGI CLASS 0-1

FIELD OF USE

- transmission
 - roller bearing
 - bearings
 - Linear guides & ball screws
 - valves
-

BUSINESS

- Automotive
 - Power Tools
 - drive technology
 - Furniture
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

- bearing manufacturer
-

FUNCTIONALITY

- Low-temperature grease
 - adhesive grease
-

PACKING

- 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com