



Grease spray FLC 367 P H1 Halal





ELKALUB FLC 367 P is a semi-synthetic EP grease spray designed as a pump spray. Due to the good creeping ability, the high adhesion and the high lubricating effect, it is very well suited for the lubrication of chains, slideways, cams, racks etc. ELKALUB FLC 367 P can also be used under the influence of water, steam, acids and alkalis (in the pH range 2-11 to 50 °C). Even after cleaning, there is often a thin film of lubricant that also protects against corrosion. ELKALUB FLC 367 P can be used in the temperature range from -20 °C to +130 °C (briefly +180 °C). The pump spray is supplied in a 300 ml can.

BASE OIL White oil

OPERATING TEMPERATURE -20 °C bis 130 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 155 mm²/s

FIELD OF USE

- bearings
- open gears
- racks
- Guides & Curves

BUSINESS

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



- print
- Food
- beverages
- Pharma & Medicine
- drive technology
- Furniture
- plant construction

FUNCTIONALITY

- Food grease
- corrosion protection
- universal

PACKING

• 300 ml pump spray

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr