



GPHC000N-40

fluid grease for gears VP 890 H1 Halal



ELKALUB VP 890 is a fluid grease for the lubrication of machine elements subject to high loads. Based on synthetic oil, the product guarantees an excellent resistance to ageing which manifests itself in a long-term lubricating effect. This is also valid for an extended temperature range as compared to products based on mineral oils. The grease is suited for oil-tight gearboxes and can easily be pumped in central lubrication systems. ELKALUB VP 890 is NSF H1 approved and can therefore be used in all areas where food, food commodity goods (e.g. packaging material) or pharmaceutical products are processed.

BASE OIL Poly-alpha-olefin**THICKENER** polyurea**VISCOSITY** 150 mm²/s**OPERATING TEMPERATURE** -35 °C bis 140 °C**NLGI CLASS** <000**FIELD OF USE**

- transmission

BUSINESS

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- print
- Food
- beverages
- Pharma & Medicine

FUNCTIONALITY

- Low-temperature grease
- Food grease
- fluid grease

PACKING

- 2 kg bag
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com