



KPHC1N-40

sliding grease GLS 993 H1 H1 Halal





ELKALUB GLS 993 H1 is a fully synthetic special grease for bearing and gear lubrication at low speeds. The grease is well suited for plastic-metal combinations and especially supports sliding movements due to its low coefficient of friction and the use of solid lubricants. ELKALUB GLS 993 H1 is preferably used for the lubrication of pneumatic cylinders. Further application examples and the use as lubricating grease can be found in fittings, taps and regulators, sliders, stamps on tablet presses and bottle filling machines. ELKALUB GLS 993 H1 is particularly suitable as assembly grease in the food sector and as a silicone-free mold release agent.

BASE OIL Poly-alpha-olefin

THICKENER Inorganic solid lubricants

VISCOSITY 400 mm²/s

OPERATING TEMPERATURE -40 °C bis 150 °C

NLGI CLASS 1

FIELD OF USE

- bearings
- Fittings & O-rings
- Pneumatics

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr



- valves
- fittings

BUSINESS

- Food
- beverages
- Pharma & Medicine
- · drive technology
- plant construction

FUNCTIONALITY

- assembly grease
- Low-temperature grease
- Food grease

PACKING

- 50 g tube
- 200 ml brush box
- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr