



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KPFHC1N-40

H1-Grease for low temperatures GLS 991 H1 Halal



ELKALUB GLS 991 is a fully synthetic low-temperature grease. Its high-quality PAO base oil and low viscosity are key to its successful performance in cold environments.

Thanks to its solid thickener, **ELKALUB GLS 991** is ideally suited for lubrication of sliding movements, such as pneumatic cylinders, valves, gates, taps, spindles, and guides. Gear lubrication with metal-metal or metal-plastic contact is also a preferred application.

The grease can also be used as a cold-temperature assembly grease, provided material compatibility is observed (e.g., not EPDM).

Its NSF H1 registration permits its use in the food industry and other hygiene-sensitive areas.

BASE OIL Poly-alpha-olefin

THICKENER Inorganic solid lubricants

VISCOSITY 46 mm²/s

OPERATING TEMPERATURE -40 °C bis 140 °C

NLGI CLASS 1

FIELD OF USE

- roller bearing

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- bearings
- Fittings & O-rings
- Pneumatics
- valves

BUSINESS

- Food
- beverages
- Pharma & Medicine
- bearing manufacturer

FUNCTIONALITY

- Low-temperature grease
- Food grease

PACKING

- 250 g tube
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com