



KPIG-10

Adhesive grease for the food industry GLS 388/N1 H1 Halal



ELKALUB GLS 388/N1 is an extremely adhesive aluminium complex soap grease based on partly synthetic base oils with a high resistance to water (also salt water). ELKALUB GLS 388/N1 is suitable for temperatures from -10 °C up to +100 °C. The main areas of application are slow-turning drive elements such as joints, shafts, open cogwheels, sliding motions in the food industry. ELKALUB GLS 388/N1 is most suitable for pairings of nonferrous metals and steel.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL White oil Poly-alpha-olefin Other

THICKENER Aluminum complex solid lubricants Others

VISCOSITY 72 mm²/s

OPERATING TEMPERATURE -10 °C bis 100 °C

NLGI CLASS 1

FIELD OF USE

- open gears

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- racks

FUNCTIONALITY

- lubricant

PACKING

- 250 g tube
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com