



KP1G-10

Adhesive grease for the food industry GLS 388/N1 H1 Halal





ELKALUB GLS 388/N1 is an extremely adhesive aluminium complex soap grease based on partly synthetic base oils with a high resistance to water (also salt water). ELKALUB GLS 388/N1 is suitable for temperatures from -10 °C up to +100 °C. The main areas of application are slow-turning drive elements such as joints, shafts, open cogwheels, sliding motions in the food industry. ELKALUB GLS 388/N1 is most suitable for pairings of nonferrous metals and steel.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL White oil Poly-alpha-olefin Other

THICKENER Aluminum complex solid lubricants Others

VISCOSITY 72 mm²/s

OPERATING TEMPERATURE -10 °C bis 100 °C

NLGI CLASS 1

FIELD OF USE

• open gears

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



racks

FUNCTIONALITY

lubricant

PACKING

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr