



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

High-performance mineral oil LFC 1022

ELKALUB EP-high-performance lubricating oils based upon mineral oil are ready-for-use lubricants with special ELKALUB additivation. They offer high protection against wear and corrosion and an excellent load carrying ability. Special inhibitors against ageing assure a long service life and safe operation. They should be used according to the viscosity prescriptions of the machine manufacturers. All oils of the ELKALUB LFC 1000 group are exempt from PCB and chlorine products and can be disposed of as normal used oils.

BASE OIL ester mineral oil

OPERATING TEMPERATURE -15 °C bis 100 °C

VISCOSITY AT 40 °C 22 mm²/s

FIELD OF USE

- open gears
- Pneumatics
- valves
- hydraulic

BUSINESS

- print
- drive technology
- Furniture
- Wood
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

FUNCTIONALITY

- Rinse oil / cleaning oil

PACKING

- 5 l jug
 - 20 l jug
 - 200 l barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com