



High-performance mineral oil with adhesive additives LFC 1100H

ELKALUB oils of the 1000 H series are CLP oils with particularly high adhesion. They are particularly suitable for lubrication points with high spin losses, e.g. Chains or open gears as well as gears and bearings in the temperature range up to 120 °C. The adhesive oils offer high wear and corrosion protection as well as excellent pressure absorption capacity. Special aging stabilizers and fine filtration ensure long service life and high operational reliability. They should be used according to the viscosity specifications of the machine manufacturer. All oils of the ELKALUB LFC 1000 H series are free of PCB and chlorine-containing compounds and can be disposed of as waste oil.

BASE OIL ester mineral oil

OPERATING TEMPERATURE -10 °C bis 120 °C

VISCOSITY AT 40 °C 100 mm²/s

FIELD OF USE

- chain
- bed ways

BUSINESS

- print
- drive technology
- Furniture
- Wood
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

FUNCTIONALITY

- lubricant

PACKING

- 5 l jug
 - 20 l jug
 - 200 l barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com