



High-performance mineral oil with adhesive additives LFC 11500H

ELKALUB oils of the 1000 H series are CLP oils with particularly high adhesion. They are particularly suitable for lubrication points with high spin losses, e.g. Chains or open gears as well as gears and bearings in the temperature range up to 120 °C. The adhesive oils offer high wear and corrosion protection as well as excellent pressure absorption capacity. Special aging stabilizers and fine filtration ensure long service life and high operational reliability. They should be used according to the viscosity specifications of the machine manufacturer. All oils of the ELKALUB LFC 1000 H series are free of PCB and chlorine-containing compounds and can be disposed of as waste oil.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL ester mineral oil Other

OPERATING TEMPERATURE -10 °C bis 120 °C

VISCOSITY AT 40 ° C 1600 mm²/s

FIELD OF USE

• chain

BUSINESS

- print
- drive technology
- Furniture
- Wood

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



- bearing manufacturer
- plant construction

FUNCTIONALITY

lubricant

PACKING

- 5 l jug
- 20 l jug
- 200 I barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr