high-performance oil LFC 34220 H1 Halal

The oils of the series ELKALUB LFC 34000 are CLP oils with high wear protection from +40 °C. This extends the wear protection requirements of the DIN standard, which are set to 80 °C, in a practical manner. The high wear protection is proven by FE 8 tests and FZG tests with the high damage power level 14 (the DIN standard requires damage power level 12). The oils of the series ELKALUB LFC 34000 offer very good corrosion protection and a high level of compatibility with NBR seals. These oils are compatible with mineral and paraffin oils as well as synthetic hydrocarbons. In order to maintain the status of the H1 approval, it must not be mixed with other oils. The main application is in the area of gear and circulation as well as chain lubrication. The temperature range is between -15 °C (-10 °C) and +120 °C.

BASE OIL ester White oil Other

OPERATING TEMPERATURE -15 °C bis 120 °C

VISCOSITY AT 40 ° C 220 mm²/s

FIELD OF USE

- transmission
- roller bearing
- bearings
- chain
- Schmitz rings

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- bed ways

BUSINESS

- print
- Food
- beverages
- Pharma & Medicine

FUNCTIONALITY

- Food grease
- circulating oil

PACKING

- 5 l jug
- 20 l jug
- 200 l barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com