

KPHC2P-40

High-temperature grease GLS 962/N2

ELKALUB GLS 962/N2 is a high-temperature grease for extremely charged bearings of high speed. In the graphic industry ELKALUB GLS 962/N2 is mainly used for vacuum-pressure pumps and blowers.

BASE OIL ester Poly-alpha-olefin

THICKENER polyurea

VISCOSITY 400 mm²/s

OPERATING TEMPERATURE -40 °C bis 170 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings
- Guides & Curves
- fittings

BUSINESS

- print
- drive technology
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

FUNCTIONALITY

- High temperature grease
- Low-temperature grease

PACKING

- 250 g tube
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com