



KPHC2P-40

High-temperature grease GLS 966/N2

BASE OIL Poly-alpha-olefin

THICKENER polyurea solid lubricants

VISCOSITY 150 mm²/s

OPERATING TEMPERATURE -40 °C bis 160 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings
- racks

BUSINESS

- Power Tools
- Wood
- bearing manufacturer

FUNCTIONALITY

- High temperature grease
- Low-temperature grease

PACKING

- 250 g tube

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 400 g cartridge
 - 1 kg can
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com