ELKALUB
Hochleistungs-Schmierstoffe
High Performance Lubricants

Chain and adhesive lubricant FLC 8 H1 H1 Halal

ELKALUB FLC 8 H1 is our chain lubricant ELKALUB FLC 8 H1 in spray form. ELKALUB FLC 8 H1 is a further development of our chain lubricant ELKALUB LA 8. The lubricating film has a good spreading capability and protects against corrosion. It has excellent boundary lubrication properties and is very adhesive and resistant to centrifugation up to 80 °C. ELKALUB FLC 8 H1 is recommended for use in heavy drive chains, cams, disk cams, open cogwheels, slideways and spindles.

BASE OIL ester Other

THICKENER polyurea

OPERATING TEMPERATURE -20 °C bis 120 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 6000 mm²/s

FIELD OF USE

- chain
- open gears
- racks
- Guides & Curves
- fittings

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

BUSINESS

- print
- Food
- beverages
- Pharma & Medicine
- drive technology
- Furniture
- Wood
- plant construction

FUNCTIONALITY

- Food grease
- noise
- lubricant
- corrosion protection

PACKING

- 400 ml of aerosol

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com