



KP3N-20

bearing grease VP 889 H1 Halal



ELKALUB VP 889 is a rolling and plain bearing grease based on a synthetic and an ester oil. Due to its relatively firm consistency and the high base oil viscosity, the grease is also suitable for the lubrication of more heavily loaded bearings at higher temperatures. A special application is the lubrication of chains in sterilizers. The well-adhering grease provides good corrosion protection and is also sufficiently resistant in a hot steam environment.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL ester White oil Poly-alpha-olefin

THICKENER Inorganic

VISCOSITY 380 mm²/s

OPERATING TEMPERATURE -15 °C bis 130 °C

NLGI CLASS 2-3

FIELD OF USE

- bearings

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

BUSINESS

- Food
- beverages
- Pharma & Medicine
- plant construction

FUNCTIONALITY

- High temperature grease
- Food grease

PACKING

- 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com