



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KPFPG1H-40

Smooth running polyglycol grease VP 885

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL polyglycol

THICKENER lithium solid lubricants

VISCOSITY 29 mm²/s

OPERATING TEMPERATURE -40 °C bis 100 °C

NLGI CLASS 1

FIELD OF USE

- transmission

BUSINESS

- Automotive
- drive technology

FUNCTIONALITY

- Low-temperature grease

PACKING

- 5 kg bucket

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com