KPF1-2K-20

MoS_2-grease GLL 10/N1-2

ELKALUB GLL 10/N1-2 is a long-fibrous, highly adhesive lubricating grease based on lithium soap and containing molybdenumdisulfide (MoS_2). ELKALUB GLL 10/N1-2 is particularly suited for heavy loads in roller and slide bearings as well as for open points of lubrication. The addition of MoS_2 to a basic grease already having a high load carrying capacity, renders ELKALUB GLL 10/N1-2 particularly suited for extremely loaded slide bearings, open cogwheels, joints, cams, rollers and slideways.

BASE OIL mineral oil

THICKENER Lithium complex

VISCOSITY 272 mm²/s

OPERATING TEMPERATURE -20 °C bis 120 °C

NLGI CLASS 1-2

FIELD OF USE

- bearings
- open gears
- racks
- Guides & Curves

BUSINESS

- Power Tools
- drive technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- plant construction

FUNCTIONALITY

- adhesive grease

PACKING

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com