



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KPFK2U-40

PFPE high-temperature grease GLS 595/N2 H1 Halal



ELKALUB GLS 595/N2 is a high temperature grease mainly used for the lubrication of roller and slide bearings in the temperature range from -40 °C up to +250 °C. ELKALUB GLS 595/N2 is resistant to acids and alkalis as well as to organic solvents. Please note: ELKALUB GLS 595/N2 may not be mixed with other lubricants. Due to its high chemical stability ELKALUB GLS 595/N2 has been used for many years as nozzle sealing compound for adhesive machines at the end of the work process. Most important: Before applying the lubricant the surfaces have to be thoroughly cleaned as the lubricant will adhere only to surfaces free of oil, grease and dirt. Recommendation: for cleaning use ELKALUB LFC 500.

BASE OIL PFPE

THICKENER solid lubricants

VISCOSITY 360 mm²/s

OPERATING TEMPERATURE -40 °C bis 250 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Fittings & O-rings
- valves

BUSINESS

- Automotive
- Food
- beverages
- Pharma & Medicine
- bearing manufacturer
- plant construction

FUNCTIONALITY

- assembly grease
- High temperature grease
- Food grease

PACKING

- 250 g tube
 - 400 g cartridge
 - 1 kg can
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com