


KPFK2U-40

# PFPE high-temperature grease GLS 595/N2 H1 Halal

ELKALUB GLS 595/N2 is a high temperature grease mainly used for the lubrication of roller and slide bearings in the temperature range from -40 °C up to +250 °C. ELKALUB GLS 595/N2 is resistant to acids and alkalis as well as to organic solvents. Please note: ELKALUB GLS 595/N2 may not be mixed with other lubricants. Due to its high chemical stability ELKALUB GLS 595/N2 has been used for many years as nozzle sealing compound for adhesive machines at the end of the work process. Most important: Before applying the lubricant the surfaces have to be thoroughly cleaned as the lubricant will adhere only to surfaces free of oil, grease and dirt. Recommendation: for cleaning use ELKALUB LFC 500.

**BASE OIL** PFPE

**THICKENER** solid lubricants

**VISCOSITY** 360 mm²/s

**OPERATING TEMPERATURE** -40 °C bis 250 °C

**NLGI CLASS** 2

**FIELD OF USE**

- roller bearing
- bearings

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Fittings & O-rings
- valves

**BUSINESS**

- Automotive
- Food
- beverages
- Pharma & Medicine
- bearing manufacturer
- plant construction

**FUNCTIONALITY**

- assembly grease
- High temperature grease
- Food grease

**PACKING**

- 250 g tube
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com