



KPPG2K-30

polyglycol grease GLS 886/N2 H1 Halal





ELKALUB GLS 886/N2 is a polyglycol grease that can be used for the lubrication of roller and plain bearings as well as the lubrication of smaller gears with a high proportion of sliding friction (e.g. worm gears).

The slight dissolving properties of ELKALUB GLS 866/N2 in relation to UV light curing products (paint, varnish, adhesives) keep lubrication points mobile.

This applies, for example, to printing machines with UV dryers and the lubrication of cam rollers and gripper shaft bearings.

In another application, ELKALUB GLS 886/N2 can be used as an assembly aid for EPDM materials.

The compatibility with other materials and the miscibility with mineral oil-based products must be checked before use.

ELKALUB GLS 886/N2 is NSF H1 registered and can therefore be used in the food industry and related hygiene-sensitive areas (pharmaceuticals, packaging, animal feed).

Former product name: VP 886

BASE OIL polyglycol

THICKENER Inorganic

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



viscosity 180 mm²/s

operating temperature -30 °C bis 120 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings
- Fittings & O-rings

BUSINESS

- print
- Food
- beverages
- Pharma & Medicine
- bearing manufacturer

FUNCTIONALITY

• Food grease

PACKING

- 250 g tube
- 100 g cartridge
- 380 g LubeShuttle
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr