

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



KPSi1R-40

silicone grease GLS 794/N1 Halal



ELKALUB GLS 794/N1 is a fully synthetic special grease for use in the food and beverage industry (sliding processes, e.g. taps, valves, fittings). The formation of the beer foam is not influenced by ELKALUB GLS 794/N1 (see report Weihenstephan). The product has good resistance to water and water vapor and can be used in the temperature range from -40 °C to + 180 °C. ELKALUB GLS 794 / N1 owns the USDA H1 Approval (occasionally allowed contact with food).

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL silicone

THICKENER solid lubricants

VISCOSITY 1000 mm²/s

OPERATING TEMPERATURE -40 °C bis 180 °C

NLGI CLASS 1

FIELD OF USE

- Fittings & O-rings

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- valves
-

BUSINESS

- Food
 - beverages
 - Pharma & Medicine
-

FUNCTIONALITY

- assembly grease
 - High temperature grease
 - Low-temperature grease
 - Food grease
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com