



KPSi2R-40

silicone grease GLS 794/N2 H1 Halal





ELKALUB GLS 794/N2 is a fully synthetic special grease for application in the food and beverage industry (sliding procedures, e.g. taps, valves, fittings). ELKALUB GLS 794/N2 does not have any influence on the formation of the beer foam (see report from Weihenstephan). The product is very resistant against water and steam and can be used for operating temperatures from -40 $^{\circ}$ C up to +180 $^{\circ}$ C. ELKALUB GLS 794/N2 is compatible with seals made of Viton, EPDM and NBR.

BASE OIL SILICONE

THICKENER solid lubricants

viscosity 750 mm²/s

OPERATING TEMPERATURE -40 °C bis 180 °C

NLGI CLASS 2

FIELD OF USE

- Fittings & O-rings
- valves

BUSINESS

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr



- Food
- beverages
- Pharma & Medicine

FUNCTIONALITY

- assembly grease
- High temperature grease
- Low-temperature grease
- Food grease

PACKING

- 50 g tube
- 200 ml brush box
- 250 g tube
- 380 g LubeShuttle
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr