



Silicone Spray FLC 710

ELKALUB FLC 710 is a low-viscosity lubricant glidant (approx. 37 mm²/s at 40 °C) is a product which is well suited for intermediate spraying during running production or for a very thin film. This film evaporates quickly. The product is mainly applied for paper and cardboard but can also be used for wood,rubber, plastics and on metal surfaces. Spray filling with: light hydrocarbons, butane.

BASE OIL SILICONE

OPERATING TEMPERATURE -50 °C bis 170 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 37 mm²/s

FIELD OF USE

- Fittings & O-rings
- Guides & Curves

BUSINESS

- print
- · drive technology
- Furniture
- bearing manufacturer
- plant construction

FUNCTIONALITY

- Lubricant / release agent
- · corrosion protection

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



• 400 ml of aerosol

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr