



KPHC2K-20

special-grease GLS 964/N2 H1 Halal





ELKALUB GLS 964/N2 is a lubricating grease with good wear and corrosion protection properties. It has been designed for use in roller and slide bearings, especially for permanently changing directions of movement. The integrated thixotropy permits the build-up of a more solid grease collar at the outer side of bearings. By that, the spin-off of grease and the penetration of foreign particles is reduced. Examples of application: gripper shafts, spindles, badly sealed bearings.

BASE OIL White oil

THICKENER polyurea

viscosity 150 mm²/s

OPERATING TEMPERATURE -25 °C bis 130 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings

BUSINESS

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



- print
- Food
- beverages
- Pharma & Medicine
- bearing manufacturer
- plant construction

FUNCTIONALITY

• Food grease

PACKING

- 250 g tube
- 100 g cartridge
- 380 g LubeShuttle
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr