



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KPFHC2N-40

special-grease GLS 980/N2 H1 Halal



ELKALUB GLS 980/N2 is a high-quality multi-purpose grease for application in roller and slide bearings, for slipways as well as for open lubrication points. Due to its synthetic oil base the grease is very resistant to ageing and can be used in a wide temperature range (-40 °C / +140 °C). **ELKALUB GLS 980/N2** is NSF H1-approved and is therefore suited for environments with food contact.

BASE OIL ester Poly-alpha-olefin

THICKENER Aluminum complex solid lubricants

VISCOSITY 220 mm²/s

OPERATING TEMPERATURE -40 °C bis 140 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings
- open gears
- Guides & Curves

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

BUSINESS

- Food
- beverages
- Pharma & Medicine
- bearing manufacturer
- plant construction

FUNCTIONALITY

- High temperature grease
- Low-temperature grease
- Food grease

PACKING

- 250 g tube
 - 100 g cartridge
 - 400 g cartridge
 - 1 kg can
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com