



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

GPOH-20

Special fluid grease for gear GLG 16/N0

ELKALUB GLG 16/N0 is a lithium saponified fluid grease with good oxidation resistance and excellent sliding friction behavior. The high load carrying capacity enables permanent lubrication of highly loaded gears.

BASE OIL mineral oil

THICKENER lithium

VISCOSITY 145 mm²/s

OPERATING TEMPERATURE -20 °C bis 100 °C

NLGI CLASS NLGI 0

FIELD OF USE

- transmission
-

BUSINESS

- print
 - Power Tools
 - Wood
-

FUNCTIONALITY

- fluid grease
-

PACKING

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

- 250 g tube
 - 1 kg can
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com