



KPFHC1K-40

Synthetic gear grease GLS 931

ELKALUB GLS 931 is a synthetic high-performance grease that is particularly suitable for gearboxes with plastic-metal combinations. The grease does not attack common gearbox plastics (PA, POM) and thereby minimizes the risk of failures due to stress corrosion cracking. Thanks to these properties, ELKALUB GLS 931 is also suitable for slide pairings with a wide variety of material combinations. ELKALUB GLS 931 is characterized by a very low coefficient of friction. In combination with the wide temperature range, the grease is ideal for applications at low temperatures. A lifetime lubrication is supported by the high quality synthetic base oil (PAO).

BASE OIL ester Poly-alpha-olefin**THICKENER** lithium solid lubricants**VISCOSITY** 150 mm²/s**OPERATING TEMPERATURE** -40 °C bis 120 °C**NLGI CLASS** 1**FIELD OF USE**

- transmission
- roller bearing
- bearings
- Linear guides & ball screws

BUSINESS

- Automotive

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Power Tools
- drive technology
- Furniture
- bearing manufacturer

FUNCTIONALITY

- Low-temperature grease
- adhesive grease

PACKING

- 250 g tube
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com