



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KP3K-20

Universal grease for bearings and gears GLL 7/N3

ELKALUB GLL 7/N3 is a lithium-saponified multipurpose grease, which is highly resistant to pressure, adhesive and resistant to oxidation. ELKALUB GLL 7/N3 has a special ELKALUB additivation for the lubrication of roller and slide bearings (under medium up to heavy loads) for temperatures from -20 °C up to +120 °C. ELKALUB GLL 7/N3 is particularly suited for points of lubrication with high centrifugal losses and where there is danger of the lubricant being washed out by water. The grease can be used up to a speed index (ndm*) of about 400.000.

BASE OIL mineral oil

THICKENER Lithium complex

VISCOSITY 97 mm²/s

OPERATING TEMPERATURE -20 °C bis 120 °C

NLGI CLASS 3

FIELD OF USE

- roller bearing
- bearings
- racks

BUSINESS

- print
- drive technology
- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- plant construction

FUNCTIONALITY

- adhesive grease
- universal

PACKING

- 250 g tube
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com