



Grease spray FLC 367 P H1 Halal



ELKALUB FLC 367 P is a semi-synthetic EP grease spray designed as a pump spray. Due to the good creeping ability, the high adhesion and the high lubricating effect, it is very well suited for the lubrication of chains, slideways, cams, racks etc. ELKALUB FLC 367 P can also be used under the influence of water, steam, acids and alkalis (in the pH range 2-11 to 50 °C). Even after cleaning, there is often a thin film of lubricant that also protects against corrosion. ELKALUB FLC 367 P can be used in the temperature range from -20 °C to +130 °C (briefly +180 °C). The pump spray is supplied in a 300 ml can.

□□ □□

□□□□ -20 °C bis 130 °C

40°C□□□□ (□□□□) 155 mm²/s

□□

- □□□□
- □□□□□□
- □□□□
- □□□□□□□□

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

☐

- ☐
- ☐
- ☐

☐

- 300☐

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com