



KP000K-10

Grease for the food industry GLS 367/N000 H1 Halal



ELKALUB GLS 367/N000 is a partly synthetic lubricating grease for application in the food industry. The product is extremely adhesive and is especially suitable for gears subject to deficient lubrication due to a spin-off of the lubricant. The product can also be applied for slowturning antifriction bearings, for slip motions and for the lubrication of chains, valves, spindles, sterilizers etc. ELKALUB GLS 367/N00 is resistant to water, acids and alkalis. ELKALUB GLS 367/N00 is suitable for temperatures from -10 °C up to +130 °C (short-time up to 180 °C).

□□ □□ □□

□□□ □□□

□□ 200 mm²/s

□□□□ -10 °C bis 130 °C

NLGI □ 000

□□

- □□□□
- □□

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□
- □□
- □□□□

□□

- □□
- □□□□

□□

- 1□□□
- 2□□□
- 18□□□□
- 50□□□□
- 150□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com