

KPFHC1N-40

H1-Grease for low temperatures GLS 991 H1 Halal

ELKALUB GLS 991 is a fully synthetic low-temperature grease. Its high-quality PAO base oil and low viscosity are key to its successful performance in cold environments.
Thanks to its solid thickener, **ELKALUB GLS 991** is ideally suited for lubrication of sliding movements, such as pneumatic cylinders, valves, gates, taps, spindles, and guides. Gear lubrication with metal-metal or metal-plastic contact is also a preferred application.
The grease can also be used as a cold-temperature assembly grease, provided material compatibility is observed (e.g., not EPDM).
Its NSF H1 registration permits its use in the food industry and other hygiene-sensitive areas.

原油	聚α烯烃
增稠剂	无机物固态润滑剂
粘性	46 mm²/s
工作温度	-40 °C bis 140 °C
NLGI级	1

应用

- 滚动轴承

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 滑动轴承
- 配件和O-型环密封圈
- 气动
- 气阀

业务

- 食品
- 饮料
- 制药和医药
- 主轴制造商

功能

- 低温
- 食品

容器

- 250克管
- 400克墨盒
- 5公斤桶
- 18公斤曲棍球
- 50公斤曲棍球
- 150公斤桶

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com