



KPFHC1N-40

H1-Grease for low temperatures GLS 991 H1 Halal



ELKALUB GLS 991 is a fully synthetic low-temperature grease. Its high-quality PAO base oil and low viscosity are key to its successful performance in cold environments.

Thanks to its solid thickener, **ELKALUB GLS 991** is ideally suited for lubrication of sliding movements, such as pneumatic cylinders, valves, gates, taps, spindles, and guides. Gear lubrication with metal-metal or metal-plastic contact is also a preferred application.

The grease can also be used as a cold-temperature assembly grease, provided material compatibility is observed (e.g., not EPDM).

Its NSF H1 registration permits its use in the food industry and other hygiene-sensitive areas.

□□ □α□□

□□□ □□□ □□□□□

□□ 46 mm²/s

□□□□ -40 °C bis 140 °C

NLGI □ 1

□□

- □□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 1000
- 1000O-10000
- 100
- 100

100

- 100
- 100
- 100000
- 100000

100

- 100
- 100

100

- 25000
- 400000
- 5000
- 1800000
- 5000000
- 150000

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com