



## KPFSi2R-40

## High-load silicone grease GLS 795/N2

ELKALUB GLS 795/N2 is a synthetic high-temperature grease for the lubrication of roller and antifriction bearings of low speed in the temperature range from -40 °C up to +200 °C. ELKALUB GLS 795/N2 is resistant to water and water vapour. In the hot air stream the application is limited to +120 °C. Attention: It is generic to silicone greases containing PTFE that there may occur explosive decomposition reactions in conveyor systems with high pressures and entrapped air. The suction of air, rapid increase in pressure as well as high pressures have to be avoided by means of suitable construction. Deaerate the whole system before putting into operation! Base oil viscosity at 25 °C: 5000 mm²/s

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

00 00000
00 4500 mm²/s
00 -40 °C bis 200 °C
NLGIO 2

- <u>|</u>||O-||||
- 🔲

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



- [[[[
- 🔲

- 🔲
- 🔲
- 🔲

- 250□□
- 400
- 5<sub>000</sub>
- 1800000
- 50
- 150<sub>00</sub>

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr