



KPHC2P-40

High-temperature grease GLS 962/N2

ELKALUB GLS 962/N2 is a high-temperature grease for extremely charged bearings of high speed. In the graphic industry ELKALUB GLS 962/N2 is mainly used for vacuum-pressure pumps and blowers.

□□ □ □α□□

□□□ □□

□□ 400 mm²/s

□□□□ -40 °C bis 170 °C

NLGI □ 2

□□

- □□□□
- □□□□
- □□□□□□□□
- □□

□□

- □□
- □□□□
- □□□□□□
- □□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

□□

- □□
- □□

□□

- 250□□
- 400□□□
- 1□□□
- 5□□□
- 18□□□□□
- 50□□□□□
- 150□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com