



High-temperature grease spray FLC 95

ELKALUB FLC 95 is a high-quality grease spray suitable for high-temperature applications. The spray is based on a synthetic hydrocarbon and a temperature-stable polyurea. Thanks to its high base oil viscosity and thickener, a sufficiently thick and adhesive lubricating film forms even at high temperatures. Permanent lubrication up to 170 °C is realistic. With regular relubrication, higher temperatures up to 220 °C are possible. Typical applications for **ELKALUB FLC 95** include the lubrication of spindles, joints, hinges, guides, chains, and open gears in hot machine environments such as shrink and drying tunnels, paint lines, or ovens of all kinds. Important: Only spray **ELKALUB FLC 95** onto cooled machine parts.

□□ □α□□

□□□ □□

□□□□ -30 °C bis 170 °C

40°C□□□□ (□□□□) 400 mm²/s

□□

- □□□□
- □□
- □□□□□□
- □□□□
- □□□□□□

□□

- □□□□
- □□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□
 - □□□□
-

□□

- □□
 - □□□
 - □□□□□□□□
 - □□□□
-

□□

- 400□□□□□□
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com