



KPSI2R-40

High-temperature silicone grease GLS 764/N2

ELKALUB GLS 764/N2 is a high temperature silicone grease. The grease is based on a high-quality, oxidation-stable silicone oil that is thickened with polyurea. In continuous operation, an application temperature of 220 °C can be achieved, which may be exceeded for a short time or with regular relubrication. ELKALUB GLS 764/N2 is suitable for the lubrication of roller and plain bearings but - due to the silicone oil base - with light loads only. Sliding applications of every kind and every material pairing are supported as best as possible. The product is adhesive and waterproof and is compatible with most plastics and sealing materials. Typical applications are heat-loaded guides, hinges, joints, sliding and ball-bearing rollers as well as bearings in hot air fans.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

000 00		
□ 80 mm²/s		
-40 °C bis 220 °C		
NLGI 2		
00		
• 0000		

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



• 0000

Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



• 0000		
• 🗓		
• 🗓		
• 250		
• 400		
• 1000		
• 5		
• 18		
• 50		

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



• 150₀₀

Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr