



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KP2K-20

High-load grease GLS 131/N2

ELKALUB GLS 131/N2 is a universal grease with high pressure absorption and very good adhesion. The grease can be used in roller and plain bearings as well as in open lubrication points. The speed characteristic in ball bearings is 250,000 mm / min-1.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

□□ □□□

□□□ □□□

□□ 320 mm²/s

□□□□ -20 °C bis 130 °C

NLGI □ 2

□□

- □□□□
- □□□□
- □□□□□□

□□

- □□□□
- □□□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 1000
- 100

100

- 100000000
- 100

100

- 25000
- 400000
- 5000
- 1800000
- 5000000
- 150000

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com