Chain and adhesive lubricant LA 8

ELKALUB LA 8 is a highly viscous special lubricant which at the same time possesses an excellent creeping ability. ELKALUB LA 8 is mainly intended for the lubrication of highly loaded chain transmissions. The very adhesive film with EP and boundary lubrication capabilities, which is formed by ELKALUB LA 8 is extremely resistant against centrifugal forces and pressure. ELKALUB LA 8 is recommended or prescribed by leading printing press manufacturers. ELKALUB LA 8 is used straight for all types of chain transmissions or as an additive (5-20 %) for mineral oils for all points of lubrication which need a particularly adhesive type of lubricant. ELKALUB LA 8 has an anti-noise effect. Examples for application: Delivery chains, guide rails, eccentrics, gripper opening curves, open gear wheels, chain guideways.

原油 酯矿物油

增稠剂 聚脲

工作温度 -5 °C bis 80 °C

40°C时的粘度 6390 mm²/s

应用

- 驱动装置
- 链条

业务

- 印刷
- 驱动技术
- 设备制造

功能

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 粘附性强的润滑剂

容器

- 1升罐
- 5升水罐
- 20升壶
- 200升桶

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com