KPF1-2K-20

MoS_2-grease GLL 10/N1-2

ELKALUB GLL 10/N1-2 is a long-fibrous, highly adhesive lubricating grease based on lithium soap and containing molybdenumdisulfide (MoS_2). ELKALUB GLL 10/N1-2 is particularly suited for heavy loads in roller and slide bearings as well as for open points of lubrication. The addition of MoS_2 to a basic grease already having a high load carrying capacity, renders ELKALUB GLL 10/N1-2 particularly suited for extremely loaded slide bearings, open cogwheels, joints, cams, rollers and slideways.

原油 矿物油

增稠剂 复合锂皂基

粘性 272 mm²/s

工作温度 -20 °C bis 120 °C

NLGI级 1-2

应用

- 滑动轴承
- 开式齿轮传动
- 齿轮齿条
- 导轨和曲线运动

业务

- 电动工具
- 驱动技术

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 设备制造

功能

- 粘附性强的润滑剂

容器

- 250克管
- 400克墨盒
- 5公斤桶
- 18公斤曲棍球
- 50公斤曲棍球

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com