

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



KPFK3U-40

PFPE high-temperature grease GLS 595/N3 H1 Halal



ELKALUB GLS 595/N3 is a high temperature grease for the lubrication of slowturning plain and antifriction bearings for temperatures from -40 °C up to +250 °C.

ELKALUB GLS 595/N3 is resistant to acids and alkalis as well as to organic solvents.

ELKALUB GLS 595/N3 may not be mixed with other lubricants. Most important: Before applying the lubricant the surfaces have to be thoroughly cleaned as the lubricant will adhere only to surfaces free of oil, grease and dirt. Recommendation: for cleaning use ELKALUB LFC 500.

□□ □□□□□

□□□ □□□□□

□□ 360 mm²/s

□□□□ -40 °C bis 250 °C

NLGI □ 3

□□

- □□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 0-10000
- 100

100

- 100
- 100
- 100
- 10000
- 10000
- 10000

100

- 100
- 100
- 100

100

- 25000
- 40000
- 5000
- 1800000
- 5000000
- 150000

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com