



KPF2K-20

Special grease GLS 163

ELKALUB GLS 163 is a short-fibrous, green grease of an increased purity and a high resistance to pressure for use in roller and antifriction bearings. The grease has a very thixotropic behaviour, which means, that the penetration values are almost 100 points lower in state of rest (the grease is more solid). This behaviour is of advantage in badly sealed bearings or in bearings with a higher tolerance. The conveyability of ELKALUB GLS 163 in central lubrication units is good. The grease does not bleed. Because of the thixotropy, the supply bin must have a follow-up piston to put the grease under pressure. Slight pressure renders the grease immediately flowable. The fine-granular, partly synthetic grease has a very flexible texture, therefore being excellently suited for small, perpetually changing alterations of guide motion. In state of rest, the grease regenerates almost to its initial values. Due to its chemical composition, ELKALUB GLS 163, under increased temperatures which can result from exterior or interior conditions, builds up Mos2. In these cases, Mos2 takes over the lubrication. The points of lubrication then look grey or black. Examples for application: Gripper shafts (also in UV and varnish areas), spindles, badly sealed slow bearings, wellsealed rapid bearings.

□□ □□□

□□□ □□ □□□□□

□□ 100 mm²/s

□□□□ -20 °C bis 130 °C

NLGI □ 1 - 2

□□

- □□□□
- □□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 1000000
- 100000

100

- 100
- 10000
- 100000

100

- 250000
- 1000000
- 380000 LubeShuttle
- 400000
- 50000
- 18000000
- 50000000
- 1500000

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com