



KP2G-20

Special adhesive grease for bearings and gears GLL 6/N2

ELKALUB GLL 6/N2 is a special grease based on mineral oil. ELKALUB GLL 6/N2 is extremely long-fibred, adhesive and resistant to pressure and centrifugal forces for temperatures from -15 °C up to +100 °C. ELKALUB GLL 6/N2 is used for the lubrication of roller bearings and gears in the low speed range (speed factor ndm < 300.000), for open gear wheels in eccentrics as well as for slow turning slide bearings. ELKALUB GLL 6/N2 has antinoise qualities and is water-resistant.

□ □ □ □

□ □ □ □ □ □

□ □ 272 mm²/s

□ □ □ □ -15 °C bis 100 °C

NLGI □ 2

□ □

- □ □ □ □
- □ □ □ □
- □ □ □ □ □ □
- □ □ □ □

□ □

- □ □ □ □

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 10000
- 100000
- 1000000

100

- 1000000000

100

- 25000
- 400000
- 50000
- 1800000
- 5000000
- 150000

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com