



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KP3K-20

Universal grease for bearings and gears GLL 7/N3

ELKALUB GLL 7/N3 is a lithium-saponified multipurpose grease, which is highly resistant to pressure, adhesive and resistant to oxidation. ELKALUB GLL 7/N3 has a special ELKALUB additivation for the lubrication of roller and slide bearings (under medium up to heavy loads) for temperatures from -20 °C up to +120 °C. ELKALUB GLL 7/N3 is particularly suited for points of lubrication with high centrifugal losses and where there is danger of the lubricant being washed out by water. The grease can be used up to a speed index (ndm*) of about 400.000.

□□ □□□

□□□ □□□□□

□□ 97 mm²/s

□□□□ -20 °C bis 120 °C

NLGI □ 3

□□

- □□□□
- □□□□
- □□□□

□□

- □□
- □□□□
- □□□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 1000

100

- 100000000
- 100

100

- 25000
- 400000
- 5000
- 1800000
- 5000000
- 150000

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com