



KP1K-20

GLS 135/N1

Spezial grease

ELKALUB GLS 135/N1 is a lithium-saponified, water resistant universal grease of high efficiency. ELKALUB GLS 135/N1 protects against corrosion and can be used for roller and slide bearings in the temperature range from -20 °C up to +120 °C. The short-fibred and homogeneous grease is excellently suitable for the lubrication of ball bearings up to a speed factor ndm of 500.000. as well as for linear units. ELKALUB GLS 135/N1 is well conveyable in central lubricating systems.

□□ □ □□□

□□□ □□□□□

□□ 100 mm²/s

□□□□ -20 °C bis 120 °C

NLGI □ 1

□□

- □□□□
- □□□□
- □□□□□□□□
- □□□□□□

□□

- □□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□□□
- □□
- □□□□□
- □□□□

□□

- □□□

□□

- 250□□
- 100□□□
- 380□LubeShuttle
- 400□□□
- 1□□□
- 5□□□
- 18□□□□□
- 50□□□□□
- 150□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com